

2 x 50 W Digital Input Closed-Loop Class-D Audio Amplifier with Audio DSP

Features

- Digital Input Signal
 - Supports I²S, LJ, RJ, TDM digital audio format inputs
 - Automatic 32 fs / 64 fs detection
 - Hardware sample rate converters (no pop-up noise by input sample rate change)
 - 8 kHz to 192 kHz sample rate support
 - Fine volume control (0.125 dB steps)
 - Supports 3.4 MHz I²C interface for quick initial setup
 - I²C address control
- Digital Signal Processing
 - Input signal mixer
 - Low power digital signal processing circuits
 - Soft mute / soft digital volume
 - 15 x 2-ch. parametric equalizers
 - Intelligent bass boost
 - Limiter and compressor
 - Multi-band DRC
 - PEQ L/R mixer function
 - Power meter
 - Special audio DSP configuration mode
- Single Chip Power Stages
 - 2-ch. x 50 W maximum audio output powers
 - Closed-loop class-D amplifier with DSP
 - 2-ch., 2.1-ch. or paralleled 1-ch. configuration
 - Two-way mono configuration with professional active crossover filters
 - Possible drive for 4 Ω loads
 - Output LC filter-less operation with internal analog feedback loop
 - Smart pulse-by-pulse current regulation to prevent shutdown at low impedance frequency point
 - THD+N < 0.01% at 1 W, 1 kHz
 - SNR 110 dB
 - N+N power DMOS output stage
 - Separated power stage power supplies for less cross-talk (inter-channel)


- Soft start and soft stop function for half-bridge pop-up controls
- Smart Analog Protections
 - Thermal protection and warning state feedback
 - Under voltage protection (UVP) for all power supplies
 - Over current protection
 - Short circuit protection: output-to-output, output-to-ground, output-to-power
 - Interrupt signal output pin
 - Fault diagnostics by I²C status register reading
- Internal Power Management Circuits
 - Programmable internal LDOs (DVDD, CVDD, LDO1)
 - Power down controls for each analog and digital block
 - Boost converter control output pin for feed-forward (three steps)
- Clock Management Circuits
 - Internal stand-alone oscillator with self-calibration
 - TCXO clock interface
 - Crystal oscillator circuit
 - High performance clock generator (low jitter fractional-N PLL)

Applications

- BT Speakers, Smart Hubs
- Sound Bars, Digital TVs
- Digital Set Top Boxes
- Car A/V Systems

Device Information

Part Number	Package	Body Size
SMA1504-F	48 - QFN	6.0 mm x 6.0 mm
SMA1504-T	48 - HSSOP (T)	6.1 mm x 12.5 mm
SMA1504-U	48 - HSSOP (B)	6.1 mm x 12.5 mm



* Technology by
Iron Device Corporation

Description

This document contains detailed target specifications for a full digital audio amplifier with switching mode four half-bridge power stages. SMA1504 is a high performance monolithic full digital amplifier with digital audio input ports. Equipped a rich set of digital signal processing functions, it can be used for digital signal inputs. The maximum audio output power is 50 W RMS per channel.